



# Q 50-100


## Bitumen UBC / Bitumen UBC Aerosol

### Characteristics

50-100 Bitumen UBS black is a durable corrosion protection based on wax/bitumen for floor pans, entry sections and wheel houses and so on. Excellent sound deadening properties, outstanding adhesion, elastic, non-sticking, high abrasion resistance and good resistance to de-icing salt.

50-100 Bitumen UBC **Aerosol** is an elastic and durable rubber-bitumen based underbody protection. Provides a long-term protection against water, salt, corrosion on corners, edges or for repair work.

### Physical Characteristics



24 month



500 ml: 2004/42/IIB(e)(840)<515  
1 kg: 2004/42/IIB(e)(840)<840

### Application 500 ml Aerosol



cleaning



shake well for  
2 min



25 cm - 30 cm



clean valve

### Application 1 kg



cleaning



5 - 10 mm  
4 - 6 bar



1 - 2




5 - 8 min




500 - 1000 µm

Consumption: 1 - 2 m<sup>2</sup>/l

### Drying



500 ml Aerosol Set to touch: 5 h



1 kg Set to touch: 2 - 4 h

### Processing tips



The floor pan must be cleaned thoroughly. It must be dry, free from dust, grease, oil and rust. Old non-adherent underbody coating must be removed. Do not spray on engine, transmission, sump, cardan shaft, exhaust pipes, axles, springs, shock absorbers, brake cables, grease nipples etc., mask this parts before!

### Storage



Store the product in a ventilated place. Keep away from direct exposure to sunlight. Keep between +15°C and 25°C.

### Safety



For more informations check the safety data sheet.



This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products. Copyright: Q-Company Int. GmbH, all rights reserved.